Get a Quote

Overview

ES0D0F48TA00 is 48-Port 10/100BASE-T Interface Card (EA, RJ45).

Quick Specification

Table 1 shows the Quick Specification.

Model	ES0D0F48TA00
Part Number	03030LXL
Description	48-Port 10/100BASE-T Interface Card (EA, RJ45)
Attributes	Hardware
Category	Hardware
Product Line	Networking
Product Family	Switch
Product Category	S7700 Interface Card
Sub Product Family	Campus Switch
Product Series	S7700
EAN	6920702727972
UOM	PCS
Pack Weight(kg)	2.5
Pack Volume(m^3)	0.0277
Pack Dimension (D*W*H mm)	502*468*118
Net Dimension (D*W*H mm)	380*378*35
Typic Power(W)	48

**Figure 1 shows the appearance of ES0D0F48TA00.**

Product Details

Figure 2 show the indicators on the ES0D0F48TA00 panel.

Note:

(1)	LINK/ACT indicator of an upper electrical port	Green	Steady on: A link has been established on the port. Blinking: The port is transmitting and receiving data.
(2)	LINK/ACT indicator of a lower electrical port		
(3)	RUN/ALM: running status indicator	Green	Steady on: The card is powered on. If the indicator is steady green for no more than 30 seconds, the CPU is being started. If the indicator is steady green for more than 30 seconds, the software is not running. Slow blinking: The card software is running properly. Fast blinking: The card software is starting.
		Red	Steady on: The card has failed and the fault requires manual intervention.
		Yellow	Steady on: The card is powered off. (For example, the card has been forcibly powered off using the power off command or is about to start.)

Figure 3 show the ports on the ES0D0F48TA00 panel.

Note:

(1)	Forty-eight 10M/100M BASE-T electrical ports

Get more information

Do you have any question about the ES0D0F48TA00 (03030LXL)?

Contact us now via info@hi-network.com.

Specification

<table>
<tr><th colspan="2">ES0D0F48TA00 Specification</th></tr>
<tr><th colspan="2">Basic Information</th></tr>
<tr><td>Model</td><td>ES0D0F48TA00</td></tr>
<tr><td>Part Number</td><td>03030LXL</td></tr>
<tr><td>Description</td><td>48-Port 10/100BASE-T Interface Card (EA, RJ45)</td></tr>
<tr><td>Level-1 category</td><td>Interface card</td></tr>
<tr><th colspan="2">Technical Specifications</th></tr>
<tr><td>Dimensions without packaging (H x W x D) [mm(in.)]</td><td>35.1 mm x 397.2 mm x 430.4 mm (1.38 in. x 15.64 in. x 16.95 in.)</td></tr>
<tr><td>Weight without packaging [kg(lb)]</td><td>2.5</td></tr>
<tr><td>Typical power consumption [W]</td><td>48</td></tr>
<tr><td>Typical heat dissipation [BTU/hour]</td><td>163.78</td></tr>
<tr><td>Maximum power consumption [W]</td><td>59</td></tr>
<tr><td>Maximum heat dissipation [BTU/hour]</td><td>201.31</td></tr>
<tr><td>Memory</td><td>256 MB</td></tr>
</table>

Want to Buy

Get a Quote

Learn More about Hi-Network | Search our Resource Library | Follow us on LinkedIn | Contact for Sales or Support

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223