

[Get a Quote](#)

Overview

The ES1D2C04HX2E provides four 100GE optical ports for data transmission and switching.

Quick Specification

Table 1 shows the quick specification.


Model	ES1D2C04HX2E
Part Number	03031YFD
Description	4-Port 100GE QSFP28 Interface Card (X2E, QSFP28)
Dimensions without packaging (H x W x D) [mm(in.)]	35.1 mm x 397.2 mm x 430.4 mm (1.38 in. x 15.64 in. x 16.95 in.)
Weight without packaging [kg(lb)]	3.15
Typical power consumption [W]	129.6
Memory	2 GB
Basic functions	Provides four 100GE optical ports for data transmission and switching.
Distributed forwarding	Performs concurrent data forwarding using a distributed data plane.
Hot swapping	Supported

Figure 1 shows the appearance of ES1D2C04HX2E.



Product Details


Figure 2 show the indicators on the ES1D2C04HX2E panel.



Note:

Number	Indicator	Color	Description
(1)	ACT	Yellow	Blinking: The port is transmitting and receiving data.
(2)	LINK	Green	Steady on: A link has been established on the port.
(3)	RUN/ALM: running status indicator	Green	Steady on: The card is powered on. If the indicator is steady green for no more than 30 seconds, the CPU is being started. If the indicator is steady green for more than 30 seconds, the software is not running. Slow blinking: The card software is running properly. Fast blinking: The card software is starting.
		Red	Steady on: The card has failed and the fault requires manual intervention.
		Yellow	Steady on: The card is powered off. (For example, the card has been forcibly powered off using the power off command or is about to start.)

Figure 3 show the ports on the ES1D2C04HX2E panel.



Note:

(1)	Four 100GE optical ports to transmit and receive service traffic at 40 Gbit/s or 100 Gbit/s
-----	---------------------------------------------------------------------------------------------

Get more information

Do you have any question about the ES1D2C04HX2E (03031YFD)?

Contact us now via info@hi-network.com.

Specification

ES1D2C04HX2E Specification	
Basic Information	
Model	ES1D2C04HX2E
Part Number	03031YFD
Description	4-Port 100GE QSFP28 Interface Card (X2E, QSFP28)
Level-1 category	Interface card
Technical Specifications	
Dimensions without packaging (H x W x D) [mm(in.)]	35.1 mm x 397.2 mm x 430.4 mm (1.38 in. x 15.64 in. x 16.95 in.)
Weight without packaging [kg(lb)]	3.15
Typical power consumption [W]	129.6
Typical heat dissipation [BTU/hour]	442.21
Maximum power consumption [W]	164.8
Maximum heat dissipation [BTU/hour]	562.31
Memory	2 GB

Want to Buy

[Get a Quote](#)

[Learn More](#) about Hi-Network

[Search](#) our Resource Library

[Follow](#) us on LinkedIn

 Contact for [Sales or Support](#)

Contact HI-NETWORK.COM For Global Fast Shipping

HongKong Office Tel: +00852-66181601

HangZhou Office Tel: +0086-571-86729517

 Email: info@hi-network.com

Skype: echo.hinetwork

WhatsApp Business: +8618057156223

